


TECHNICAL SPECIFICATION

TYPE OF EXTINGUISHER	Water type
CAPACITY	9.0L +0% -5%
CARTRIDGE WEIGHT	950g
OVERALL WEIGHT	14.0kg +0% -5%
VOLUME	11.4L
MATERIAL THICKNESS (CYL)	1.6mm
MIN TENSILE STRENGTH	200N/mm (200MPa)
MIN. TEST PRESSURE	25bar (350,990kPa) min 30s
MIN. BURST PRESSURE	35bar (500,990kPa)
DISCHARGE TIME	90 - 90s
CLASS OF FIRE	1.3A
TEMPERATURE RANGE	+5°C To +50°C
DESIGN	Manufactured and approved to EN-3
FINISHING	Rod

• - Not shown in drawing

ITEM	PART NO	DESCRIPTION	MATERIAL	QTY
1	FEC228-01	CARTRIDGE VALVE M74	CHROME PONGE BRASS CE188	1
2	FEC034-PS-BK	ADAPTOR	NYLON	1
3	OR6614-RB	O-RING M74	NCT 66YARN 30009	1
4	FEC007-PS-GLT-BK	DISCHARGE HOSE GL-GLTH 486,0mm	NITILE 70	1
5	FEC027-MS	CLIP AS	NYLON	1
6	FEC181-PS-GLT	DISCHARGE NOZZLE GL (DRP-07.0)	NYLON 6	1
7	FEC096-MS-EN	BASE RING	MILD STEEL	1
8	FEC117-PS-EN	PULL TAG BROOKS 6M	P.P	1
9	FEC099-MS	SAFETY PIN	STAINLESS STEEL	1
10	FEC098-MS	HECK RING M74	MILD STEEL	1
11	FEC008-MS-GLT-RO	CYLINDER GL WATER CARTRIDGE - RED	COLD ROLLED STEEL	1
12	FEC008-PS-GLT	DIP TUBE GL LOTH (67W STRAINER 470mm)	P.V.C	1
13	FEC017-PS-GLT-RO	CYLINDER DELT GL - RED	P.P	1
14	FEC103-PS-GLT	STRAINER	ABS	1
15	FEC014-CS-095-PL	COB CARTRIDGE 66mm - PLASTIC COATING	CARBON STEEL	1
16	OR6014-RB-BK	O-RING Ø14.10 12.48 x 1.781- ADAPTOR	NITILE 70	1
17	FEC094-PS-BK	BASE SKIRTING	LDPE	1
18	FEC232-MS	BRACKET GL	MILD STEEL	1



VIKING
ULTRAVIOLET PROTECTANT

UNLESS OTHERWISE STATED
DIMENSION IN MILLIMETERS

APPROVAL I
APPROVAL II

APPROVAL I
APPROVAL II

APPROVAL I
APPROVAL II

APPROVAL I
APPROVAL II

APPROVAL I	APPROVAL II	APPROVAL I	APPROVAL II	APPROVAL I	APPROVAL II
APPROVAL I	APPROVAL II	APPROVAL I	APPROVAL II	APPROVAL I	APPROVAL II
APPROVAL I	APPROVAL II	APPROVAL I	APPROVAL II	APPROVAL I	APPROVAL II
APPROVAL I	APPROVAL II	APPROVAL I	APPROVAL II	APPROVAL I	APPROVAL II
APPROVAL I	APPROVAL II	APPROVAL I	APPROVAL II	APPROVAL I	APPROVAL II

EURO FIRE EXTINGUISHER

9L EURO CARTRIDGE WATER TYPE ASSEMBLY