



NOTES:

1. ALL ELECTRIC WIRING BY YARD.
2. ALL FIELD WELDS TO BE PERFORMED ACC. TO APPROVED WPS (YARD RESPONSIBILITY).
3. HYDRAULIC POWER UNIT TO BE LOCATED BY YARD NOT MORE THAN 10 PIPE METERS FROM DAVIT AT SAME DECK LEVEL.
4. CENTER OF GRAVITY FOR DAVIT ONLY. FOR BOAT COG PLEASE REFER TO BOAT DRAWINGS.
5. ACCESS & BOARDING PLATFORMS, WALKWAYS, HANDRAILS ETC - YARD SUPPLIED
6. FOR LIFEBOAT DAVIT PERFORMANCE DETAILS SEE DAVIT TECHNICAL SPECIFICATION.
7. FOR REACTION FORCES IN DECK SEE SEPERATE REPORT.
8. DAVIT TOTAL WEIGHT (EXCLUDING BOAT) 17 T.

1	Issued for construction	PGO	GNI	GNI	02.08.2018
REV	DESCRIPTION	BY	CHECK	APPRO	DATE
REVISION HISTORY					
		VIKING Norsafe Life-Saving Equipment Norway AS P. O. Box 115 4852 Faervik NORWAY Tel: +47 37 05 85 00 Fax: +47 37 05 85 01 24/7 Service: +47 37 05 63 33 Email: viking@viking-life.com			
		This drawing is the sole property of VIKING Norsafe Life-Saving Equipment Norway AS. It must not be submitted to other parties nor used in any manner detrimental to our interests. It shall not be copied, reproduced, used for manufacturing or sale without the written consent of VIKING Norsafe Life-Saving Equipment Norway AS. All rights are reserved.			
DWG SIZE: A3	SCALE: 1:100	COPY OF:	PART NO.:	WEIGHT: 17000,000 kg	SHEET: 1 / 1
CLIENT NO.:	PROJECTION METHOD:		LH-230 LIFEBOAT DAVIT WITH MAXIMA 120 PORTSIDE GENERAL ARRANGEMENT		
TOLERANCES: ISO 2768-mk, ISO 13920-BF	REVISION: 1				
DWG No.: G-502734	PROJECT:				