



VIKING
PPE

MARCH 2025

Lifejackets



YouSafe™ Pro | SOLAS/CE



MODEL
VIKING YouSafe™ Pro

VIKING YouSafe™ Pro

The stylish and ergonomic VIKING YouSafe™ Pro is a safe and extremely versatile choice for all professional maritime and offshore applications. This tough lifejacket is also available as part of safety agreement exchange programs.

- Dual approved for cross-application use
- Ergonomic design with excellent finish and appearance
- Double buoyancy chamber and great in water performance

VIKING YouSafe™ Pro, inflatable lifejacket, SOLAS/MED, CE/ISO, MSMER
Product number: PV9341





VIKING
PPE

MARCH 2025

Lifejackets



YouSafe™ Pro | SOLAS/CE



Specifications

Approvals

- SOLAS/MED
- CE/ISO
- MSMER

Cover fabric

- Flame retardant coated polyester
- Wipe clean

Colour options

- Red/black, red/black wipe clean, high-vis yellow/black, high-vis yellow/black wipe clean

Design features

- Ergonomic design with excellent finish and appearance
- Several options for customization
- Double buoyancy chamber (available with 180N symmetrical, 275N symmetrical or 275N-asymmetrical buoyancy)
- Excellent in-water performance
- Unique VIKING cleat-attachment system for easy service and replacement
- Zipper with reflective trim
- Emergency light, buddy line, whistle and lifting strap included
- Fully compatible with VIKING anti-exposure and work suits
- Fully compatible with standard harness systems (including versions used in the offshore wind industry)

Typical applications

- Cargo vessels
- Passenger ships
- Fishing vessels
- Offshore

Features

- Halkey Roberts® or Hammar® inflation system
- Sprayhood
- PLB - including the option of a class M approved PLB
- D-ring/harness
- Print
- Embroidery

Service interval

Annually as per SOLAS regulations



Related items

VIKING YouSafe™ Cyclone, constant wear work suit, SOLAS/CE (PS4116)

VIKING YouSafe™ Hurricane, anti-exposure suit, SOLAS/CE (PS4190)

FOR FURTHER INFORMATION

WWW.VIKING-LIFE.COM

VIKING LIFE-SAVING EQUIPMENT
Protecting people and business