

Viking Norsafe RCH36 Combi hook

Product particulars:

Combined release mechanism for
rescue boats and/or liferafts
Cable operated remote release mechanism for
rescue boats and/or liferafts
RCH36
36 KN (SWL)

 Recommended structure MBL>6 x SWL of Liferaft/Rescue boat
Applicable Material Diameter of Rings (Masterlink/Shackle): 18mm ~ 26mm
Explanation of padlock label positions:



Locked position when the hook is fully reset



Hook is open or in automatic release mode position (Hook is not locked)

n		۱

С

D

Revised note 2, lifting ring/masterlink/shackle diameter range based on PHLI JO							JOZH	THWA	06.12.2021	1
new/additional testing PHLI							JOZH	INWA	00.12.2021	
	REASON FOR ISSUE				В	Y	CHECK	APPRO	DATE	1
			REVISION	I HISTORY	Ý					\vdash
				VIKING N	orsafe	Life-	Saving	Equipme	ent Norway AS	1
		VIKING	P.O Box 115 Tel: +47 37 05 85 00 4852 Færvik Fax: +47 37 05 85 01							
		NORSA		NORWAY 24/7 Service: +47 37 05 63 33 Email: Viking-Norsafe@viking-life.com						
		NOK5P		Drawn by					release date	-
	AVING EQUIPMENT			JKJI	SH	-	JOEZ	·	9.05.2020	
	number	Project name			С	lient nur	nber		1	
	Material Number									
	136 CON	ABI HOOK								
							W	Weight 10.0 kg		A
									<u> </u>	-
Projection method										
	ERAFT AND RESCUE BOAT									
								Sheet Size	1	
eral arrangement ISO 2768-mK, ISO 13920-BF 1:4 A3										
g Number							R	evision	Sheet No.]
()3837							1	1/1	
							1			

is the sole property of VIKING Norsafe Life-Saving Equipment Norway AS. It must not be submitted to other parties nor used in any manner detrimental s. It shall not be copied, reproduced, used for manufacturing or sale without the written consent of VIKING Norsafe Life-Saving Equipment Norway AS.