

3		2		1		1	1
	-						н
	■ Mr						
		IVIZ Z					G
							_
			, ;•				F
							E
AWING SHOWS POR CTRIC WIRING FROM D WELDS TO BE PERI RD RESPONSIBILITY) TO CLASS APPR. PRI D WELDS MARKED V	EL-CABI ORMED . ALL FIE OR TO V	INET TO DAN ACC. TO AF LD WELDIN WELDING.	PRO G IS	VED			\square
INSTALLATION. NGTHS: E 1: 20.5m + (H+H1 E 2: 23.5m + (H+H1 HT FROM STOWAGE DITIONAL HEIGHT DU	.) + 3m E TO L.W		Л				D
N STEEL TO BE S355, SUITABLE FOR -20°C. FITTING STEEL TO BE S 235 SUITABLE FOR -20°C. ATION OF PIN LASHING TO BE FINALIZED AFTER LIFE STALLATION (TO BE ALIGNED WITH BOAT LASHING BRACKETS).							с
							-
ISSUED FOR CONSTRUCTION DESCRIPTIO NC		SION HISTORY	MIM BY		JJB APPRO		В
VIKING NORS		P.O. Box 115 4852 Færvik NORWAY This drawing is the sole prope must not be submitted to othe It shall not be copied, reprodu consent of VIKING Norsafe Li PART NO.	rty of VIKING r parties nor u ced, used for i	Tel: +47 37 Fax: +47 3 24/7 Servic Email: vikir Norsafe Life-S sed in any man manufacturing	7 05 85 00 7 05 85 01 ce: +47 37 ng@viking- aving Equipm nner detriment or sale withou	05 63 33 life.com ent Norway AS. It al to our interests. t the written are reserved.	
A1 1:25 S0 2768-mk, ISO 13920-BF		DAVIT TYF STARBOA FOR MAGO GENERAL	PE C- RD V GIE 1	ERSI 0.7 TI	ON ELB	^{SHEET} 1 /1	A
3		2				1	